## **Product Information**

PI 102 1814



# micrologic® PREMIUM 102

## Synthetic Active Oil

Unique, synthetic oil with adhesive effect for lasting lubrication.







### **Properties:**

- No gumming or sticking
- Excellent corrosion protection
- Clear with a pleasant aroma
- High penetration effect with very short ventilation time
- Compatible with all sealant materials
- Temperature stable from –40°C up to +150°C

#### Area of application:

- On every inspection and service inspection
- Especially suitable for miniature precision components
- In any situation where grease is neither suitable nor desirable
- Use with small mechanical components
- Excellent for freeing track rods, joints and lock cylinders

#### **Application:**

Shake can briefly and spray surfaces to be treated from a distance of some 20 cm. Can also be used at below-zero temperatures

#### **Authorised TUNAP Centre**













www.aetautoworld.wix.com/aetautoworld

TUNAP | Chemistry with drive.

<b>Product Description</b>	Quantity	Article Number	Packaging Unit
Synthetic Active Oil	Aerosol canister 300ml	MP 10200300AB	24

Data and information contained herein are the result of careful test. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith and believed to be accurate. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products. Further, you expressly understand and agree that the date and information hereunder are given gratis and we assume no obligation or liability. The product information is only valid in the latest version.